



WMS WEIGHT MEASUREMENT SYSTEM SPECIFICATIONS DATA SHEET

"ALL GEC Products are Made in the USA"

Operating Temperature	14°F (-10°C) to 104°F (40°C)
Storage Temperature	-35°F (-37°C) to 150°F (66°C)
Internal Power Requirements	7.2 VDC (6x AA NiMH Rechargeable/ Disposable)
External Power Requirements	100-240 VAC, 47-63 Hz charger

Options	<ul style="list-style-type: none"> • Automatic Backlight Sensor • Data Acquisition Interface • Seamless Data Transfer • Weight Management Software Including Center of Balance • Durable Wireless Handheld Unit • Detachable Ramps and Spacers • Multiple Scale Configuration (2,4,6,8) • Storage Case
---------	--

Dimension

Overall Length	20-1/2" inches (52 cm)
Overall Width	14" inches (35.5 cm)
Height	3-1/4" inches (8.3 cm)

Weighing Surface

Length	14-1/4" inches (36 cm)
Width	10-1/8" inches (26 cm)

Weight 40 lbs (18.1 kgs)

Capacity 0 to 20,000 lbs (0 to 10,000 Kgs)

Features

- Solar Power Enhanced Battery Life
- NTEP Approved Shear Beam Loadcells
- User Selectable Increments
- Waterproof Membrane Switch and Enclosure
- Foldable Handles for Storage
- Rugged Design
- 6 AA Disposable or Rechargeable Batteries—400 Hours
- Mil-Spec Storage & Transportation Case



Accuracy (per NIST Handbook 44 for Class III devices)

0 to 2,500 lbs	± 50lbs.
2,500 to 10,000 lbs	± 100lbs.
10,500 to 20,000 lbs	± 150lbs.

PROPRIETARY NOTICE

This document contains information which concerns or relates to trade secrets, processes, operations, pricing, style of work apparatus, or to identity, confidential statistical data amount source or any income, profits, losses or expenditures of General Electrodynamics Corporation. Such information is being submitted in confidence with the understanding that it will not be disclosed to third parties in whole or part without the express written consent of an officer of General Electrodynamics Corp.
(Reference Trade Sec. Rets Act, 18U.S.C. 1905)

WMS